



17	SURGE PROTECTOR	-
16	DRIVER	-
15	LED MODULE ASYMMETRICAL LENS (1)	-
14	GROMMET $\varnothing 8-10$	EPDM
13	COUPLER MOUNTING SIDE ENTRY	ZINC-PLATED STEEL
12	COUPLER MOUNTING POST-TOP	ZINC-PLATED STEEL
11	28 LED SUPPORT	STEEL SHEET
10	GEARTRAY	GALVANIZED STEEL
9	SECURITY COVER RETAINER	STAINLESS STEEL DIPSTICK
8	CLOSING LATCH	STAINLESS STEEL PLATE
7	SEALING GASKET	SILICONE
6	GLASS SEALING GASKET	SILICONE
5	CURVED GLASS "GC"	TOUGHENED
4	SIDE/POST-TOP FASTENING CLAMP	PRESSURE DIE CAST, AI
3	REFLECTOR SUPPORT PLATE "A"	PRESSURE DIE CAST, AI
2	COVER	PRESSURE DIE CAST, AI
1	BODY	PRESSURE DIE CAST, AI
ITEM	NAME	MATERIAL

(1) FEATURES	
COLOR TEMPERATURE	4000 K
RA	75
NUMBER OF LEDS	28
TOTAL WORKING FLUX	2430 lm
TOTAL POWER CONSUMPTION	34,5 W
SYSTEM EFFICIENCY	70 lm/W
NOTES: INFORMATION RELATING TO T_a OF 25°C OPERATING CURRENT: 350 mA	

	Date	Signature
Drawn:	14-06-12	FCV
Checked:		
Approved:		

C.&G. CARANDINI, S.A.
BARCELONA MADRID



LUMINAIRE: PCM.A.GC.L034

N. 11290-E

Replaces:

Replaced by: