



| | | |
|------|---------------------------------|--------------------------|
| 17 | SURGE PROTECTOR | - |
| 16 | DRIVER | - |
| 15 | LED MODULE SYMMETRICAL LENS (1) | - |
| 14 | GROMMET $\varnothing 8-10$ | EPDM |
| 13 | COUPLER MOUNTING SIDE ENTRY | ZINC-PLATED STEEL |
| 12 | COUPLER MOUNTING POST-TOP | ZINC-PLATED STEEL |
| 11 | 28 LED SUPPORT | STEEL SHEET |
| 10 | GEARTRAY | GALVANIZED STEEL |
| 9 | SECURITY COVER RETAINER | STAINLESS STEEL DIPSTICK |
| 8 | CLOSING LATCH | STAINLESS STEEL PLATE |
| 7 | SEALING GASKET | SILICONE |
| 6 | GLASS SEALING GASKET | SILICONE |
| 5 | CURVED GLASS "GC" | TOUGHENED |
| 4 | SIDE/POST-TOP FASTENING CLAMP | PRESSURE DIE CAST, AI |
| 3 | REFLECTOR SUPPORT PLATE "A" | PRESSURE DIE CAST, AI |
| 2 | COVER | PRESSURE DIE CAST, AI |
| 1 | BODY | PRESSURE DIE CAST, AI |
| ITEM | NAME | MATERIAL |

| (1) FEATURES | |
|--|---------|
| COLOR TEMPERATURE | 4000 K |
| RA | 75 |
| NUMBER OF LEDS | 28 |
| TOTAL WORKING FLUX | 2660 lm |
| TOTAL POWER CONSUMPTION | 34,5 W |
| SYSTEM EFFICIENCY | 77 lm/W |
| NOTES: INFORMATION RELATING TO T_a OF 25°C OPERATING CURRENT: 350 mA | |

| | Date | Signature |
|-----------|----------|-----------|
| Drawn: | 14-06-12 | FCV |
| Checked: | | |
| Approved: | | |

C.&G. CARANDINI, S.A.
BARCELONA MADRID



LUMINAIRE: PCM.DS.GC.L034

N. 11291-E

Replaces:

Replaced by: